

トラクター オイル等諸元一覧

トラクタ形式	エンジン形式	エンジン 出力	PTO 出力	燃料 タンク	冷却水	エアークリーナ	エンジン オイル	パワステ	ミッション オイル	リア 終減速	フロント デフ	フロント 終減速	ノズル セット圧	備考
		PS/rpm	PS/rpm	ℓ	ℓ	ℓ	ℓ	ℓ	ℓ	片側ℓ	ℓ	片側ℓ	kg/cm ²	
MF 130	A4-107	30/2250	24/685	45	9.5	0.6	5.82	—	19.0	0.35	—	—	135	
MF 135	AD3-152	46/2200	39/721	48	10.2	0.7	6.8	0.5	25.0	—	—	—	170	
MF 145	AD3-152	46/2200	39/721	48	10.2	0.7	6.8	0.5	28.5	1.7	—	—	170	
MF 165	A4-212	60/2000	57/635	79	10.8	0.7	9.09	0.9	28.5	1.7	—	—	175	
MF 175	A4-236	69/2200	63/690	79	14.0	0.7	7.1	0.9	40.0	1.7	—	—	175	
MF 185	A4-248	76/2000	65/615	79.5	13.6	0.7	7.96	0.85	29.56	1.7	—	—	170	
MF 154	AD3-152S	52/2300	44/636	60.5	10.2	0.5	6.8	1.9	21.0	2.1	4.5	1.5	170	
MF 174	A4-236	69/2200	62/657	60.5	15.0	0.7	7.1	1.9	21.0	2.1	4.5	1.5	175	
MF 194	A4-248	76/2100	71/660	60.5	15.0	0.7	7.1	1.9	21.0	2.1	4.5	1.8	175	
MF 1104	A6-354	95/2300	89/1095	92	22.0	1.2	13.0	4.0	23.5	2.0	11.5	2.7	190	
MF 240	AD3-152	48/2250	44/721	60	10.2	—	6.9	0.5	32.0	1.7	4.5	2.1	175	
MF 240S	AD3-152	48/2250	44/721	68	10.2	—	5.7	0.5	43.40	—	4.5	0.2	175	
MF 254	AD3-152	52/2250	45/720	60.5	10.5	—	6.9	1.9	36.0	1.5	4.5	2.1	175	
MF 265	A4-236	66/2100	63/635	80	14.0	—	7.1	0.9	40.0	1.7	11.0	1.9	175	
MF 275	A4-236	71/2100	64/690	80	14.0	—	7.1	0.9	35.0	1.7	11.0	1.9	185	
MF 290	A4-248S	79/2200	72/664	90	14.0	—	8.0	1.9	40.0	3.1	11.0	1.9	175	
MF 295	A4-318	95/2350	81/670	105	16.5	—	9.7	1.0	38.5	2.9	—	1.8	185	
MF 354F	AD3-15S	48/2250	44/625	62	10.5	0.5	6.7	1.5	33.0	3.6	3.6	1.5	175	
MF 362	A4-236	66/2200	63/592	75	14.4	0.2	7.5	—	45.0	—	4.5	1.2	171	
MF 365	A4-236	62/2200	54/680	105	15.1	0.2	7.5	1.2	47.4	2.5	5.0	1.2	190	
MF 374H	A4-236	66/2200	62/611	62	15.5	0.5	7.1	1.5	33.0	3.6	3.6	1.5	175	
MF 382	A4-248	79/2200	73/601	75	14.4	0.2	7.5	—	45.0	—	4.5	1.2	185	
MF 390	A4-248S	79/2200	68/655	105	15.1	0.2	7.5	1.2	47.4	2.9	5.0	1.2	195	
MF 390T	AT4-236	88/2200	81/627	105	15.5	0.2	7.7	—	47.4	—	5.0	1.2	232	
MF 394F	A4-248S	79/2100	73/658	62	15.5	0.5	7.1	1.5	33.0	3.6	3.6	1.5	175	
MF 394HS	A4-248S	79/2200	75/619	62	15.5	0.5	7.1	1.5	33.0	3.6	3.6	1.5	175	
MF 396	1006-6	98/2200	93/1100	118	24.9	0.2	14.3	—	44.4	2.9	12.5	左に含む	223	
MF 399	A6-354.4	98/2200	86/1090	118	23.0	0.2	14.3	—	47.4	2.9	5.8	1.3	195	
MF 690	A4-248S	79/2200	68/668	145	14.2	—	8.0	1.2	36.5	3.1	11.0	1.6	190	
MF 698	A4-318.2	93/2100	81/658	145	15.9	—	9.7	2.8	36.5	3.1	11.0	1.8	190	
MF 699	A6-354	95/2200	82/10100	145	19.5	—	15.4	1.0	36.0	3.1	11.0	1.8	195	
MF 2680	ATC6-354	135/2400	128/1178	228	27.0	—	19.0	—	85.01	—	11.0	1.8	195	
MF3050	A4-236	69/2200	63/650	148	16.0	—	7.5	—	60.0	—	5.8	1.4	195	
MF 3060	A4-248S	79/2200	72/656	148	16.0	—	7.5	—	60.0	—	5.8	1.4	190	
MF 3065	AT4-236	88/2200	74/657	148	16.0	—	7.5	—	60.0	—	5.8	1.4	235	
MF 3075	1004-4THR2	95/2200	91/1037	190	19.4	—	8.5	—	64.0	—	6.5	1.8	250	
MF 3080	A6-354.4	98/2200	92/1090	190	25.1	—	9.0	—	60.0	—	6.5	1.8	220	
MF 3085	1006-6HR	104/2200	96/1105	190	25.0	—	19.0	—	64.0	—	6.5	1.8	220	
MF 3090	A6-354.4	107/2200	102/1120	190	25.0	—	16.6	—	60.0	—	6.5	1.8	200	
MF 3095	1003-6HR	108/2200	100/1100	190	25.0	—	19.0	—	64.0	—	6.5	1.8	220	
MF 31	251006-6T	126/2200	120/1095	220	25.5	—	19.0	—	64.0	—	11.0	1.8	210	
MF 3655	1006-6TW	155/2200	148/1120	246	27.0	—	19.0	—	85.0	5.0	11.0	1.8	210	
MF 3680	T612-DS	180/2200	173/1100	306	29.5	—	23.5	—	85.0	5.0	11.0	1.8	180	
MF 4225	4.41	65/2200	57/624	127	17.0	—	6.5	—	50.0	—	11.5	0.8	23.0	

トラクター オイル等諸元一覧

トラクタ形式	エンジン形式	エンジン出力	PTO出力	燃料タンク	冷却水	エアークリーナ	エンジンオイル	パワステ	ミッションオイル	リア終減速	フロントデフ	フロント終減速	ノズルセット圧	備考
		PS/rpm	PS/rpm	ℓ	ℓ	ℓ	ℓ	ℓ	ℓ	片側ℓ	ℓ	片側ℓ	kg/cm ²	
MF 6120	4.41	80/2200	73/1102	130	17.0	—	7.4	—	62.0	—	6.0	1.0	240	
MF 6130	1004.4T	88/2200	79/1079	130	17.0	—	7.4	—	62.0	—	14.0	—	240	
MF 6140	1004.4T	90/2200	85/1013	130	17.0	—	7.4	—	62.0	—	6.0	1.0	250	
MF 6150	1004.4T	95/2200	91/1037	160	17.0	—	7.4	—	62.0	—	6.0	1.2	270	
MF 6160	1006.6	104/2200	96/1105	160	25.0	—	15.0	—	62.0	—	6.0	1.2	240	
MF 6170	1006.6T	115/2200	103/993	160	25.0	—	15.0	—	68.0	—	6.7	2.0	240	
MF 6180	1006.6T	125/2200	115/1002	160	25.0	—	15.0	—	68.0	—	6.7	2.0	250	
MF 8130	1006.6T	145/2200	145/1010	286	25.0	—	19.0	—	80.0	—	117	2.0	223	
MF 281	SC	85/2200	76/623	75	14.5	—	7.0	—	43.0	—	6.0	0.5	240	
MF 292	SD	105/2200	97/623	160	24.0	—	8.0	—	47.0	—	6.0	0.5	240	
MF 481	1104C-44	82/2200	72/612	75	14.5	—	9.0	—	43.0	—	5.5	0.5	302	
MF 492	1104C-44T	99/2200	92/610	160	18.4	—	9.0	—	45.0	—	7.5	0.5	302	
MF 2210	903-27	54/2300	49.1/600	53	10.0	0.5	7.5	—	35.0	4.0	3.5	0.7	296	
MF 2220	903-27	64/2300	60.6/589	53	10.0	0.5	7.5	—	35.0	4.0	3.5	0.7	296	
MF 2430	804C-33T	69/2500	59.3/540	90	10.0	0.9	11.5	—	35.0	4.0	3.5	1.5	195	
MF 2435	804C-33T	76/2500	67.4/540	90	10.0	0.9	11.5	—	35.0	4.0	5.0	1.5	195	
MF 2440	804C-33T	82/2500	73.3/540	90	10.0	0.9	11.5	—	35.0	4.0	5.0	1.5	195	
MF 3615	33DT	58/2150	45.0	¹⁰⁸ ₈₃	11.0	—	10.5	—	39.0	—	5.5	0.6	278	
MF 3625	33DT	69/2150	55.0	¹⁰⁸ ₈₃	11.0	—	10.5	—	39.0	—	5.5	0.6	278	
MF 3635	33DT	79/2150	65.0	¹⁰⁸ ₈₃	11.0	—	10.5	—	39.0	—	5.5	0.6	278	
MF 3645	33DTA	92/2150	75.0	¹⁰⁸ ₈₃	11.0	—	10.5	—	39.0	—	5.5	0.6	278	
MF 4235	4.41	75/2200	65/625	127	17.5	—	6.5	—	50.0	—	5.6(11.5)	0.8	230	
MF 4245	1004C4T	85/2200	76/609	127	17.5	—	6.5	—	50.0	—	5.6(11.5)	0.8	222	
MF 4255	1004C4T	95/2200	89/1001	127	17.5	—	6.5	—	50.0	—	5.6(12.5)	0.8	253	
MF 4270	1006C6	110/2200	105/1030	202	28.0	—	13.5	—	50.0	—	7.6	1.2	220	
MF 4445	44DT	88/2270	73.2/624	70	15.5	—	9.0	—	32.0	—	6.5	0.8	278	DL901 場合高さ調節必要
MF 4455	44DT	98/2280	86.9/646	70	15.5	—	9.0	—	32.0	—	6.5	0.8	278	DL901 場合高さ調節必要
MF 5435	1104C-44	72/2200	65.1/1000	150	16.6	—	7.5	—	74.0	—	5.5	0.9	302	
MF 5445	1104C-44T	85/2200	75.9/1000	150	16.6	—	7.5	—	74.0	—	5.5	0.9	302	
MF 5455	1104C-44T	95/2200	85.9/1000	200	16.6	—	7.5	—	74.0	—	5.5	0.9	302	
MF 5465	1106C-E60TA	110/2200	101.7/1000	230	25.0	—	14.5	—	68.0	—	6.0	0.7	302	
MF 6245	1004.4T	85/2200	82/1030	130	17.0	—	7.4	—	72.0	—	6.0	0.9	294	
MF 6255	1004.4T	95/2200	87/1100	160	17.0	—	7.4	—	72.0	—	6.8	1.1	294	
MF 6260	1006.6	105/2200	94/1100	160	25.0	—	15.0	—	72.0	—	6.8	1.1	294	
MF 6265	1004.4T	105/2200	97/1102	160	17.0	—	7.4	—	72.0	—	6.8	1.1	294	
MF 6270	1006.6T	115/2200	105/1015	225	25.0	—	15.0	—	72.0	—	7.0	1.5	294	

トラクター オイル等諸元一覧

トラクタ形式	エンジン形式	エンジン 出力	PTO 出力	燃料 タンク	冷却水	エアー クリーナ	エンジン オイル	パワステ	ミッション オイル	リア 終減速	フロント デフ	フロント 終減速	ノズル セット圧	備考
		PS/rpm	PS/rpm	ℓ	ℓ	ℓ	ℓ	ℓ	ℓ	片側ℓ	ℓ	片側ℓ	kg/cm ²	
MF 6280	1006.6T	125/2200	120/1000	225	25.0	—	15.0	—	72.0	—	7.0	1.5	294	
MF 6290	1006.6T	135/2200	128/1000	225	28.5	—	15.6	—	72.0	—	10.2	1.6	294	
MF 6445	1104C-44T	85/2200	74.5/1000	200	28.0	—	8.0	—	60.0	—	5.5	0.9	302	
MF 6455	1104C-44T	95/2200	89.1/1004	200	28.0	—	8.0	—	60.0	—	5.5	0.9	302	
MF 6460	1104C-E44TA	105/2200	103.1/1003	200	28.0	—	8.0	—	60.0	—	6.8	1.1	302	
MF 6470	1104C-E44TA	115/2200	107.5/1005	200	28.0	—	8.0	—	60.0	—	6.8	1.1	302	
MF 6465	1106C-E60TA	110/2200	102.4/1001	270	28.0	—	14.5	—	71.0	—	8.5	0.6	302	
MF 6475	1106C-E60TA	125/2200	114.9/1000	270	28.0	—	14.5	—	71.0	—	8.5	0.6	302	
MF 6480	1106C-E60TA	135/2200	122.4/1000	270	28.0	—	14.5	—	71.0	—	8.5	0.6	302	
MF 6485	66ETA	145/2200	133.1/1000	380	28.0	—	20.0	—	109.0	—	6.0	1.5	278	
MF 6490	66ETA	160/2200	142.6/1016	380	28.0	—	20.0	—	109.0	—	6.0	1.5	278	
MF 6495	66ETA	175/2200	166.7/1000	380	28.0	—	20.0	—	109.0	—	6.0	1.5	278	
MF 7465	1106C-E60TA	110/2200	101/1007	270	28.0	—	14.5	—	71.0	—	8.5	0.6	302	
MF 7475	1106C-E60TA	125/2200	109.4/1001	270	28.0	—	14.5	—	71.0	—	8.5	0.6	302	
MF 7480	1106C-E60TA	135/2200	127/1000	270	28.0	—	14.5	—	71.0	—	8.5	0.6	302	
MF 7485	66ETA	145/2200	128.7/1000	380	28.0	—	20.0	—	109.0	—	6.0	1.5	278	
MF 7490	66ETA	160/2200	142.3/1000	380	28.0	—	20.0	—	109.0	—	6.0	1.5	278	
MF 7495	66ETA	175/2200	161.9/1000	380	28.0	—	20.0	—	109.0	—	6.0	1.5	278	
MF 8220	1006.6T	155/2200	135/1053	410	28.5	—	15.6	—	157.0	3.6	10.2	1.6/1.8	294	
MF 8240	620D	170/2200	145/1053	410	34.0	—	20.0	—	150.0	3.6	10.2	1.6/1.8	270	
MF 8250	634D	185/2200	160/1053	410	34.0	—	19.0	—	147.0	4.5	10.2	1.6/1.8	270	
MF 8260	634D	210/2200	180/1053	410	34.0	—	19.0	—	156.0	4.5	10.2	1.6/1.8	270	
MF 5445T3	1104D-E44TA	95/2200	80/2000	190	25	—	10	—	70.0	—	9	0.7	1600	
MF 5455T3	1104D-E44TA	101/2200	93/2000	190	25	—	10	—	70.0	—	9	0.7	1600	
MF 5460T3	1104D-E44TA	117/2200	103/2000	190	25	—	10	—	70.0	—	9	0.7	1600	
MF 5465T3	1106D-E66TA	120/2200	115/2000	215	25	—	17	—	70.0	—	9	0.8	1600	
MF 5470T3	44CWA	128/2200	113/2000	200	25	—	13.5	—	70.0	—	9	0.8	1400	
MF 5475T3	1106D-E66TA	135/2200	129/1800	215	25	—	17	—	70.0	—	9	0.8	1600	
MF 5480T3	49CWA	140/2200	123/2000	200	25	—	13.5	—	70.0	—	9	0.8	1400	
MF 6445T3	1104D-E44TA	95/2200	88/2000	190	28	—	10	—	70.0	—	6.0/8.5	0.7	1600	
MF 6455T3	1104D-E44TA	105/2200	100/2000	190	28	—	10	—	70.0	—	6.0/8.5	0.7	1400	
MF 6460T3	44CWA	115/2200	110/2000	190	28	—	10	—	70.0	—	6.0/8.5	0.7	1600	
MF 6465T3	1106D-E66TA	120/2200	115/2000	270	28	—	17	—	70.0	—	6.0/8.5	0.7	1400	
MF 6470T3	49CWA	125/2200	120/2000	190	28	—	10	—	70.0	—	6.0/8.5	0.7	1600	
MF 6475T3	1106D-E66TA	135/2200	130/2000	270	28	—	17	—	70.0	—	6.0/8.5	0.7	1600	
MF 6480T3	1106D-E66TA	145/2200	140/2000	270	28	—	17	—	70.0	—	6.0/8.5	0.7	1600	
MF 5465T3	66CTA	121/2200	115/2000	215	25	—	17	—	70.0	—	6.0/8.5	0.7	1600	
MF 5475T3	66CTA	132/2200	129/2000	215	25	—	17	—	70.0	—	6.0/8.5	0.7	1600	

トラクター オイル等諸元一覧

トラクタ形式	エンジン形式	エンジン 出力	PTO 出力	燃料 タンク	冷却水	エアー クリーナ	エンジン オイル	パワステ	ミッション オイル	リア 終減速	フロント デフ	フロント 終減速	ノズル セット圧	備考
		PS/rpm	PS/rpm	ℓ	ℓ	ℓ	ℓ	ℓ	ℓ	片側ℓ	ℓ	片側ℓ	kg/cm ²	
MF 6465T3	66CTA	121/2200	115/2000	270	28	—	17	—	70.0	—	6.0/8.5	0.7	1600	
MF 6475T3	66CTA	132/2200	128/2000	270	28	—	17	—	70.0	—	6.0/8.5	0.7	1600	
MF 6480T3	66CTA	147/2200	140/2000	270	28	—	17	—	70.0	—	6.0/8.5	0.7	1600	
MF 6485T3	66CTA	162/2200	160/2000	380	28	—	20	—	70.0	—	6.0/8.5	1.5	1600	
MF 6490T3	66CTA	170/2000	170/2000	380	28	—	20	—	70.0	—	6.0/8.5	1.5	1600	
MF 6495T3	66CTA	182/2200	180/2000	380	28	—	20	—	70.0	—	6.0/8.5	1.5	1600	
MF 7465T3	1106D-E66TA	120/2200	115/2000	270	28	—	17	—	50.0	5	6.0/8.5	0.8	1600	油圧 100ℓ
MF 7475T3	1106D-E66TA	130/2200	128/2000	270	28	—	17	—	50.0	5	6.0/8.5	0.8	1600	油圧 100ℓ
MF 7480T3	1106D-E66TA	145/2200	140/2000	270	28	—	17	—	50.0	5	6.0/8.5	0.8	1600	油圧 100ℓ
MF 7485T3	66CTA	162/2200	160/2000	370	28	—	20	—	58.0	—	6.0/8.5	1.8	1600	油圧 100ℓ
MF 7490T3	66CTA	170/2000	170/2000	370	28	—	20	—	58.0	—	6.0/8.5	1.8	1600	油圧 100ℓ
MF 7495T3	66CTA	182/2200	180/2000	370	28	—	20	—	58.0	—	6.0/8.5	1.8	1600	油圧 100ℓ
MF 5608D4	33AWI	82/2200	73/1800	165	14.5	—	13	—	70.0	—	5	0.8	1600	
MF 5609D4	33AWI	91/2200	83/1800	165	14.5	—	13	—	70.0	—	5	0.8	1600	
MF 5610D4	33AWI	102/2200	90/2000	165	14.5	—	13	—	70.0	—	5	0.8	1600	
MF 6612D4	49AWI	110/2200	105/2000	250/30	24.5	—	18	—	60.0	—	9	0.8/2.0	1800	
MF 6613D4	49AWI	120/2200	115/2000	250/30	24.5	—	18	—	60.0	—	9	0.8/2.0	1800	
MF 6614D4	49AWI	130/2200	125/2000	250/30	24.5	—	18	—	60.0	—	9	0.8/2.0	1800	
MF 6615D6	49AWI	140/2200	135/2000	250/30	24.5	—	18	—	65.0	—	9	0.8/2.0	1800	
MF 6616D6	49AWI	150/2200	140/2000	250/30	24.5	—	18	—	65.0	—	9	0.8/2.0	1800	
MF 6616DV	49AWI	150/2200	140/2000	250/30	24.5	—	14	—	52.0	13	9	0.8/2.0	1800	油圧 100ℓ
MF 7614D4	66AWI	130/2100	115/2000	310/30	26	—	18.5	—	60.0	—	9	0.8/2.0	1800	
MF 7615D4	66AWI	140/2100	125/2000	310/30	26	—	18.5	—	65.0	—	9	0.8/2.0	1800	
MF 7615D6	66AWI	140/2100	134/2000	310/30	26	—	18.5	—	65.0	—	9	0.8/2.0	1800	
MF 7616D6	66AWI	150/2100	140/2000	310/30	26	—	18.5	—	65.0	—	9	0.8/2.0	1800	
MF 7616DV	66AWI	150/2100	140/2000	310/30	26	—	18.5	—	65.0	13	9	0.8/2.0	1800	油圧 100ℓ
MF 7618D6	66AWI	165/2100	155/2000	310/30	26	—	18.5	—	65.0	—	9	0.8/2.0	1800	
MF 7618DV	66AWI	165/2100	150/2000	310/30	26	—	18.5	—	65.0	13	9	0.8/2.0	1800	油圧 100ℓ
MF 7620D6	66AWI	185/2100	180/1950	430/40	26	—	20	—	90.0	—	12	2.4	1800	
MF 7620DV	66AWI	185/2100	180/1950	430/40	26	—	23	—	52.0	13	11	2.4	1800	油圧 100ℓ
MF 7622D6	74AWI	200/2100	194/1950	430/40	26	—	23	—	95.0	—	13	2.4	1800	
MF 7622DV	74AWI	200/2100	195/1950	430/40	26	—	23	—	52.0	13	13	2.4	1800	油圧 100ℓ
MF 7624D6	74AWI	220/2100	210/1950	430/40	26	—	23	—	95.0	—	13	2.4	1800	
MF 7624DV	74AWI	220/2100	205/1950	430/40	26	—	23	—	52.0	13	13	2.4	1800	油圧 100ℓ
MF 5711SL D6	44AWFC	101/2200	90.0/2000	180/25	13.7	—	12	—	75	—	5	0.8	1600	
MF 5713SL D6	44AWFC	127/2200	109.0/2000	180/25	13.7	—	12	—	75	—	5	0.8	1600	
MF 7715D4	66AWF	169/2100	135/2000	245/30	23.25	—	18.5	—	70	—	9	0.7/2.2	2000	
MF 7716D6	66AWF	181/2100	140/2000	245/30	23.25	—	18.5	—	70	—	9	0.7/2.2	2000	

トラクター オイル等諸元一覧

トラクタ形式	エンジン形式	エンジン出力	PTO出力	燃料タンク	冷却水	エアー クリーナ	エンジン オイル	パワステ	ミッション オイル	リア 終減速	フロント デフ	フロント 終減速	ノズル セット圧	備考
		PS/rpm	PS/rpm	ℓ	ℓ	ℓ	ℓ	ℓ	ℓ	片側ℓ	ℓ	片側ℓ	kg/cm ²	
MF 7718D6	66AWF	192/2100	155/2000	245/30	23.25	—	18.5	—	70	—	9	0.7/2.2	2000	
MF 7718DV	66AWF	192/2100	155/2000	245/30	23.25	—	23	—	64	19	9	0.8/2.2	2000	
MF 7720D6	66AWF	215/2100	180/1800	295/40	28.0	—	20	—	101	—	9	2.2/2	2000	
MF 7720DV	66AWF	215/2100	180/1800	295/40	28.0	—	20	—	64	—	9	2.2/2	2000	
MF 7722DV	74AWF	230/2100	195/1800	295/40	28.0	—	23	—	64	19	9	2.2/2	2000	
MF 7724D6	74AWF	247/2100	210/1800	295/40	28.0	—	23	—	101	—	9	2.2/2	2000	
MF 7724DV	74AWF	247/2100	210/1800	295/40	28.0	—	23	—	64	19	9	2.2/2	2000	
MF 7726D6	74AWF	260/2100	230/2000	295/40	28.0	—	23	—	101	—	9	2.2/2	2000	
MF 7726DV	74AWF	260/2100	230/2000	295/40	28.0	—	23	—	64	19	9	2.2/2	2000	
MF 4707C	33AWIC	72/2200	55.3/1800	120	11	—	12.5	—	43.0	—	5.5	0.9	1600	
MF 4707F	33AWIC	72/2200	55.3/1800	105	11	—	12.5	—	43.0	—	5.5	0.9	1600	
MF 4709C	33AWFC	95/2200	73.1/2000	120/14	11	—	12.5	—	43.0	—	5.5	0.9	1600	
MF 4709F	33AWFC	95/2200	73.1/2000	105/10	11	—	12.5	—	43.0	—	5.5	0.9	1600	
MF 5710C	44AWFC	97/2200	76.0/2000	153/18	16	—	15	—	48.0	—	5	0.9	1600	
MF 5710F	44AWFC	97/2200	76.0/2000	145/13.5	15	—	15	—	48.0	—	5	0.9	1600	
MF 6713C	44AWFC	127/2200	101.7/1800	153/18	16	—	15	—	48.0	—	5	0.9	1600	
MF 6713F	44AWFC	127/2200	101.7/1800	170/13.5	15	—	16	—	40.0	—	5	0.9	1600	
MF 6713S D4	49AWF	150/2100	110/1800	205/30	26	—	18.5	—	70.0	—	9	0.8	2000	
MF 6713S DV	49AWF	150/2100	110/1800	205/30	26	—	18.5	—	48.0	19	9	0.8	2000	
MF 6714S D6	49AWF	158/2100	120/2000	205/30	26	—	18.5	—	70.0	—	9	0.8	2000	
MF 6714S DV	49AWF	158/2100	120/2000	205/30	26	—	18.5	—	48.0	19	9	0.8	2000	
MF 6716S D6	49AWF	182/2100	140/1800	205/30	26	—	18.5	—	70.0	—	9	0.8	2000	
MF 6716S DV	49AWF	182/2100	140/1800	205/30	26	—	18.5	—	48.0	19	9	0.8	2000	
MF 6718S D6	49AWF	190/2100	155/2000	205/30	26	—	18.5	—	70.0	—	9	0.8	2000	
MF 6718S DV	49AWF	190/2100	155/2000	205/30	26	—	18.5	—	48.0	19	9	0.8	2000	
F513VARIO S4	TCD4.1 L4	120/2100	117/1800	280/31	31	—	10	—	28	10	8.2		1800	
F516VARIO S4	TCD4.1 L4	150/2100	147/1800	280/31	31	—	10	—	28	10	8.2		1800	
F716VARIO S4	TCD6.1 L6	148/2100	144/1800	400/38	29	—	16.5	—	47	17	8.5		1800	
F718VARIO S4	TCD6.1 L6	165/2100	161/1800	400/38	29	—	16.5	—	47	19	8.5		1800	
F720VARIO S4	TCD6.1 L6	185/2100	181/1800	400/38	29	—	16.5	—	47	19	8.5		1800	
F722VARIO S4	TCD6.1 L6	205/2100	201/1800	400/38	29	—	16.5	—	47	19	8.5		1800	
F724VARIO S4	TCD6.1 L6	220/2100	216/1800	400/38	29	—	16.5	—	47	19	8.5		1800	
F927VARIO S4	TTCD7.8 L6	267/2100	173/1700	600/36	32	—	36	—	67	17	36(1),17.5(2)		2300	(1)1系統ブレーキ(2)2系統ブレーキ
F930VARIO S4	TTCD7.8 L6	297/2100	192/1700	600/36	32	—	36	—	67	17	36(1),17.5(2)		2300	(1)1系統ブレーキ(2)2系統ブレーキ
F933VARIO S4	TTCD7.8 L6	325/2100	210/1800	600/36	32	—	36	—	67	17	36(1),17.5(2)		2300	(1)1系統ブレーキ(2)2系統ブレーキ
F936VARIO S4	TTCD7.8 L6	358/2100	222/1800	600/36	32	—	36	—	67	17	36(1),17.5(2)		2300	(1)1系統ブレーキ(2)2系統ブレーキ
F939VARIO S4	TTCD7.8 L6	388/2100	240/1900	600/36	32	—	36	—	67	17	36(1),17.5(2)		2300	(1)1系統ブレーキ(2)2系統ブレーキ
F1038VARIO S4	D2676LE529	400/1950	263/1500	800/85	32	—	47	—	90	18	14.5		1800	

トラクター オイル等諸元一覧

トラクタ形式	エンジン形式	エンジン出力	PTO出力	燃料タンク	冷却水	エアー クリーナ	エンジン オイル	パワステ	ミッション オイル	リア 終減速	フロント デフ	フロント 終減速	ノズル セット圧	備考
		PS/rpm	PS/rpm	ℓ	ℓ	ℓ	ℓ	ℓ	ℓ	片側ℓ	ℓ	片側ℓ	kg/cm ²	
F1042VARIO S4	D2676LE529	439/1950	285/1500	800/85	32	—	47	—	90	18	14.5		1800	
F1046VARIO S4	D2676LE529	480/1950	318/1500	800/85	32	—	47	—	90	18	14.5		1800	
F1050VARIO S4	D2676LE529	520/1950	341/1500	800/85	32	—	47	—	90	18	14.5		1800	
MF 4506	E854F	62/2200		100	13	—	8	—	①60②58	—	8	—	160	①L型式②L型式以外
MF 4507	E854F	70/2200		100	13	—	8	—	①60②58	—	8	—	160	①L型式②L型式以外
MF 4508	E854E	88/2200		88	13	—	8	—	①60②58	—	①10②8	—	160	①L型式②L型式以外
MF 4509	E854E	88/2200		100	13	—	8	—	①60②58	—	①10②8	—	160	①L型式②L型式以外
MF 4510	E854E	98/2200		100	13	—	8	—	①60②58	—	①10②8	—	160	①L型式②L型式以外
MF 4511	WDR-CPS4-TJW20	108/2200		190	8.1	—	8	—	80	—	①15.5②11.3	—	160	①J型式以外②J型式
MF 4512	WDR-CPS4-TJW20	120/2200		190	8.1	—	8	—	80	—	①15.5②11.3	—	160	①J型式以外②J型式
MF 1777	E33AWIC-75	77/2200		100	11.5	—	12.5	—	58	—	8	—	160	
MF 1787	E33AWIC-85	87/2200		100	11.5	—	12.5	—	58	—	10	—	160	
MF 1797	E33AWIC-95	97/2200		100	11.5	—	12.5	—	58	—	10	—	160	
MF 1775M	E33AWFC-70	72.1/2200		110/15	11.5	—	12.5	—	58	—	8	—	160	
MF 1785M	E33AWFC-85	87/2200		110/15	11.5	—	12.5	—	58	—	10	—	160	
MF 1795M	E33AWFC-95	97/2200		110/15	11.5	—	12.5	—	58	—	10	—	160	
MF 1755E	N4LDI-TA	54/2600		53	7.1	—	6.5	—	40	—	8.5	—	200	
MF 1765M	N4LDI-TA	60/2600		53	7.1	—	6.5	—	40	—	8.5	—	200	
MF 1726	E4DG	95/2200		105	8	—	12	—	①60②58	—	①10②8	—	—	①L型式②L型式以外
MF 1724	E4DG	85/2200		105	8	—	12	—	①60②58	—	①10②8	—	—	①L型式②L型式以外
MF 1723	E4DG	75/2200		105	8	—	12	—	①60②58	—	①10②8	—	—	①L型式②L型式以外
MF 1720	E4DG	68/2200		90	8	—	12	—	①60②58	—	8	—	—	①L型式②L型式以外
MF 1718	E4DG	58/2200		90	8	—	12	—	①60②58	—	8	—	—	①L型式②L型式以外
MF 1730	CPS4	116.5/2200		190	12.1	—	8.0	—	80	—	15.5	—	160	
MF 1728	CPS4	101.4/2200		190	12.1	—	8.0	—	80	—	15.5	—	160	